

## MODEL 30 SPECIFICATIONS



Model	a. E30DPL b. E30DEL c. E30DTL	d. E30DTEL e. E30DRL f. E30DR
Shaft Length mm (in) / Color	a. / b. / c. / d. / e. 508 (20") Blue f. 381 (15") Blue	
Weight kg (lbs)	a. 80 (177) / b. 71 (156) / c. 83 (183) / d. 73 (162) / e. 68 (150) / f. 66 (146)	
Engine Type	Inline 2-cylinder E-TEC Direct Injection	
Bore x Stroke mm (in)	76 x 64 (2.992 x 2.500)	
Displacement cc (cu in)	578 (35.3)	
Ignition System	IDI Fast Rise Inductive Ignition	
Starter	a. / b. / c. / d. Electric e. / f. Rope	
Trim Method	a. / c. Power Trim and Tilt b. / d. / e. / f. Manual Tilt	
Propshaft kilowatts (HP)*	22 kw (30 HP) @ 5500 RPM	
Full Throttle Operating Range	5000-6000 RPM	
Gear Ratio	2.15:1	
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode	
Alternator	Variable Voltage Computer Controlled 56 Amp** / 750 watt output with Regulator	
Cooling	Pressure and Temperature Controlled Water Cooled	
Steering	a. / b. Remote or Accessory Tiller c. / d. / e. / f. Tiller standard	
Limited Warranty	3 Years Non-Declining	
Emissions Compliance	EPA CARB 3 STAR European Union	



\* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

\*\* 56 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 15 Amp.